

GENERAL NOTES

- ALL WORK SHALL BE PERFORMED IN ACCORDANCE WITH ALL STATE, COUNTY AND LOCAL CODES, REGULATIONS AND ORDINANCES. MATERIAL, EQUIPMENT, INSTALLATION, AND PROCEDURES SHALL BE IN STRICT ACCORDANCE WITH THE APPLICABLE REQUIREMENTS OF THE LATEST CURRENT EDITION OF THE REFERENCED DOCUMENTATION.
- A. REGULATIONS OF LOCAL AUTHORITIES HAVING JURISDICTION.
- B. NFPA-NATIONAL FIRE PROTECTION ASSOCIATION.
- C. SMACNA SHEET METAL AND AIR CONDITIONING NATIONAL ASSOCIATION.
- D. ASME AMERICAN SOCIETY OF MECHANICAL ENGINEERS. E. ASTM - AMERICAN SOCIETY OF TESTING AND MATERIALS.
- F. ASHRAE AMERICAN SOCIETY OF HEATING, REFRIGERATION AND AIR CONDITIONING ENGINEERS, INC. LATEST EDITION OF STANDARD 15.
- L. INTERNATIONAL EXISTING BUILDING CODE 2018.
- M. INTERNATIONAL BUILDING CODE 2018.
- N. INTERNATIONAL ENERGY CONSERVATION CODE 2018. O. INTERNATIONAL MECHANICAL CODE - 2018.
- P. INTERNATIONAL PLUMBING CODE 2018.
- Q. SMACNA SHEET METAL AND AIR CONDITIONING NATION ASSOCIATION.
- CONTRACTORS SHALL BE RESPONSIBLE TO VERIFY AND FAMILIARIZE THEMSELVES WITH ACTUAL FIELD CONDITIONS ASSOCIATED WITH WORK UNDER THIS CONTRACT PRIOR TO SUBMITTING THEIR BID.
- . ELEVATIONS NOTED ARE TO CENTER LINES OF PIPES FOR ALL PRESSURE LINES AND TO INVERT FOR ALL GRAVITY FLOW
- PROVIDE ISOLATION VALVES AS INDICATED ON THE DRAWINGS, DETAILS AND AS REQUIRED SO THAT EQUIPMENT AND INSTRUMENTS IN THE SYSTEM CAN BE ISOLATED FOR SERVICE AND MAINTENANCE.
- 5. PROVIDE AN AIR VENT AT THE HIGH POINT OF EACH DROP IN THE CHILLED WATER SYSTEM.
- 6. UNLESS OTHERWISE NOTED, ALL PIPING IS OVERHEAD, TIGHT TO UNDERSIDE OF SLAB AND STRUCTURE, WITH SPACE FOR INSULATION, IF REQUIRED.
- INSTALL PIPING SO THAT ALL VALVES AND DAMPERS ARE ACCESSIBLE.
- 8. MAINTAIN MINIMUM 6'-8" CLEARANCE TO UNDERSIDE OF PIPES, DUCTS, CONDUIT, SUSPENDED EQUIPMENT, ETC., THROUGHOUT ACCESS ROUTES IN MECHANICAL AND ELECTRICAL ROOMS.
- 9. CERTAIN ITEMS SUCH AS CLEAN-OUTS, ACCESS DOORS, RISES AND DROPS IN DUCTWORK AND PIPING, ETC., ARE INDICATED ON THE DRAWINGS FOR CLARITY OR A SPECIFIC LOCATION REQUIREMENT AND SHALL NOT BE INTERPRETED AS THE EXTENT OF THE REQUIREMENTS FOR THOSE ITEMS. THE CONTRACTOR SHALL BE RESPONSIBLE FOR THESE ITEMS AS REQUIRED ELSEWHERE IN THE CONTRACT DOCUMENTS.
- 10. EQUIPMENT CONNECTION SIZES MAY DIFFER FROM INDICATED PIPE SIZES. PROVIDE APPROPRIATE TRANSITIONS WHERE
- . THE DRAWINGS ARE DIAGRAMMATIC AND ALL OFFSETS, FITTINGS, TRANSITIONS AND ACCESSORIES ARE NOT NECESSARILY SHOWN. COORDINATE THE INSTALLATION OF ALL PIPING, EQUIPMENT AND OTHER WORK WITH ALL OTHER TRADES.
- 12. IT IS THE INTENT THAT ALL WORK SHALL BE COMPLETE IN EVERY RESPECT AND THAT MATERIAL OR WORK SPECIFICALLY NOT INDICATED ON THE DRAWINGS, BUT NECESSARY TO COMPLETE THE WORK, SHALL BE PROVIDED.
- 13. ALL AUTOMATIC TEMPERATURE CONTROL SETPOINTS SHALL BE ADJUSTABLE.
- 14. PROVIDE A MINIMUM OF 36-INCHES OF CLEARANCE TO ALL EQUIPMENT AT THE ELECTRICAL COMPONENT LOCATIONS.
- 15. CONTRACTOR IS PROHIBITED FROM ATTACHING TO THE ROOF DECK AND LOWER CHORD OF JOISTS AS A SUPPORT SYSTEM FOR DEVICES AND BUILDING SYSTEMS.
- 16. CONTRACTOR SHALL REPAIR ALL PENETRATION HOLES IN WALLS, FLOORS, CEILINGS AND ROOF AS A RESULT OF DEMOLITION WORK. REPAIRS SHALL MATCH ADJACENT CONSTRUCTION.
- '. PROVIDE ALL NECESSARY COMPONENTS FOR U.L. LISTED THROUGH PENETRATION SYSTEM AT RATED WALL PENETRATIONS IN ORDER TO MAINTAIN THE REQUIRED ASSEMBLY RATING. REFER TO ARCHITECTURAL DRAWINGS FOR RATED ASSEMBLY LOCATIONS AND CONSTRUCTION.
- 18. MECHANICAL CONTRACTOR SHALL PROVIDE P/T PORTS ADJACENT TO ALL TEMPERATURE SENSORS FOR VERIFICATION TESTING. COORDINATE WITH THE ATC CONTRACTOR FOR LOCATIONS.
- 19. REFRIGERANTS SHALL BE RECOVERED FROM ALL REFRIGERATION EQUIPMENT IN ACCORDANCE WITH ARI AND SPA STANDARDS. RECOVERED REFRIGERANT SHALL BE PLACED IN APPROVED CONTAINERS LABELED IN ACCORDANCE WITH ARI AND EPA STANDARDS AND TURNED OVER TO THE OWNER.

GENER	RAL MECHANICAL LEGENI
SYMBOL	DEFINITION
Ø	DIAMETER
•	CONNECT TO EXISTING
	DEMOLITION ENDS HERE
#	DRAWING NOTE DESIGNATION
Ø	FLAT OVAL

SYMBOL	DEFINITION
—CHS——	CHILLED WATER SUPPLY
— — CHR — —	CHILLED WATER RETURN
— CHS(P) —	CHILLED WATER SUPPLY (PRIMARY)
CHS(S)—	CHILLED WATER SUPPLY (SECONDARY)
CHR(P)	CHILLED WATER RETURN (PRIMARY)
CHR(S)	CHILLED WATER RETURN (SECONDARY)
CW	COLD WATER
—HS——	HEATING SUPPLY
— —HR— —	HEATING RETURN
—HS(P)——	HEATING SUPPLY (PRIMARY)
—HS(S)——	HEATING SUPPLY (SECONDARY)
— -HR(P)- —	HEATING RETURN (PRIMARY)
— -HR(S)- —	HEATING RETURN (SECONDARY)
—CD—	CONDENSATE DRAIN LINE
—NPW —	NON-POTABLE WATER
—	GAS
—— SAN ———	SANITARY
	EXPANSION LOOP
x%	PITCH OF PIPE, % SLOPE
c——	PIPE-TURN DOWN
o <u> </u>	PIPE-TURN UP
	PIPE DROP INTO
	PIPE TAP INTO BOTTOM 2-LINE PIPE DOWN
o	2-LINE PIPE DOWN 2-LINE PIPE UP
<u> </u>	SOLENOID VALVE
	END CAP
	BLIND FLANGE
<u> </u>	DIRECTION OF FLOW
	GATE VALVE
	GLOBE VALVE
—	BALL VALVE
<u> </u>	BALANCING VALVE
	MULTI-PURPOSE VALVE
	CHECK VALVE
	BUTTERFLY VALVE
————	3-WAY MODULATING VALVE (ATC)
—ऄ—	2-WAY MODULATING VALVE (ATC)
₽	PRESSURE REDUCING VALVE
<u> </u>	NEEDLE VALVE
₩	PRESSURE RELIEF OR SAFETY VALVE
	HOSE END DRAIN VALVE
	STRAINER W/HOSE END DRAIN VALVE & CAP
\square_1	AUTOMATIC AIR VENT
<u> </u>	FLOW METER FITTING
$-\otimes$	COMBINATION SHUT-OFF/BALANCING VALVE
	UNION
	FLANGE
	CONCENTRIC REDUCER
	ECCENTRIC REDUCER
	FLEXIBLE CONNECTION (PIPING)
	MANUAL AIR VENT
<u></u>	THERMOMETER
, —	PRESSURE GAUGE W/NEEDLE VALVE
H⊢⊚	TRESSURE GAUGE WAREFULE VALVE

MECH	ANICAL ABBREVIATIONS
ABBREV	DESCRIPTION
AAV ABR	AUTOMATIC AIR VENT ABOVE FINISHED ROOF
ACCH ACU	AIR-COOLED CHILLER AIR CONDITIONING UNIT
ACV AD	AUTOMATIC CONTROL VALVE ACCESS DOOR
ADJ AFF AMS	ADJACENT/ADJUSTABLE ABOVE FINISHED FLOOR AIR FLOW MEASURING STATION
AHU ALT	AIR HANDLING UNIT ALTERNATE
ANC APD	ANCHOR AIR PRESSURE DROP
APG APPROX	AIR PRESSURE GAUGE APPROXIMATE
ARCH AS	ARCHITECTURAL AIRFLOW SENSOR/AIR SEPARATOR
ATC AV	AUTOMATIC TEMPERATURE CONTROLS ACID VENT/AIR VENT
AVG AW BAS	AVERAGE ACID WASTE BUILDING AUTOMATION SYSTEM
BFP BHP	BACKFLOW PREVENTOR BRAKE HORSEPOWER
BLDG BTU	BUILDING BRITISH THERMAL UNIT
BTUH BWF	BRITISH THERMAL UNIT PER HOUR BYPASS WATERFILTER
BWV CAP	BACK WATER VALVE CAPACITY
CC CD	COOLING COIL CONDENSATE DRAIN
CFH CFM	CUBIC FEET PER HOUR CUBIC FEET PER MINUTE
CIP	CAST IRON CAST IRON PIPE
CIRC CL CLG	CIRCULATING CENTERLINE CEILING/COOLING
CO CO ₂	CLEANOUT/CARBON MONOXIDE SENSOR CARBON DIOXIDE SENSOR
COMB COMP	COMBUSTION COMPRESSOR
COND COP	CONDENSATE/CONDENSER/CONDENSING COEFFICIENT OF PERFORMANCE
CPVC CR	CHLORINATED POLYVINYL CHLORIDE CONDENSER WATER RETURN
CS CV	CONDENSER WATER SUPPLY/CURRENT SENSOR CONSTANT VOLUME
CW D	COLD WATER DAMPER/DEEP/DIA/DROP
DB DEG	DECIBEL/DRY BULB DEGREES
DESIG DIA DN	DESIGNATION DIAMETER DOWN
DOAS DP	DEDICATED OUTSIDE AIR SYSTEM DEW POINT/DIFFERENTIAL PRESSURE
DPS DSHP	DIFFERENTIAL PRESSURE SWITCH/SENSOR DUCTLESS SPLIT HEAT PUMP
DSS DWG	DUCTLESS SPLIT SYSTEM DRAWING
DWGS DWH	DRAWINGS DOMESTIC WATER HEATER
E EA	EAST/ELECTRICAL EACH/EXHAUST AIR
EAF EAT EER	EXHAUST AIR FAN ENTERING AIR TEMPERATURE ENERGY EFFICIENCY RATIO
EF EFF	EXHAUST FAN EFFICIENCY
EFT EL	ENTERING FLUID TEMPERATURE ELEVATION
ELEC ELEV	ELECTRIC/ELECTRICAL ELEVATION/ELEVATOR
EMER EMS	EMERGENCY ENERGY MANAGEMENT SYSTEM
EQ EQUIP ES	EQUAL EQUIPMENT EMERGENCY STATION
ESP ESS	EXTERNAL STATIC PRESSURE EMERGENCY SHUTDOWN SWITCH
ET ETR	EXPANSION TANK EXISTING TO REMAIN
EVAP EWT	EVAPORATOR ENTERING WATER TEMPERATURE
EX EXH	EXISTING EXHAUST
EXP EXT	EXPANSION EXTERIOR EAUDENIHEIT/EAN/EIDE/EIDE LINE/EDEEZECTAT
FA FC	FAHRENHEIT/FAN/FIRE/FIRE LINE/FREEZESTAT FACE AREA/FREE AREA FLEXIBLE CONNECTION
FCO FCU	FLOOR CLEANOUT FAN COIL UNIT
FD FDV	FIRE DEPARTMENT VALVE
FF FLA	FINISHED FLOOR FULL LOAD AMPS
FLR FM	FLOOR FLOW METER/FACTORY MUTUAL GLOBAL
FOR	FLAT ON BOTTOM FUEL OIL RETURN
FOS FPD FPM	FUEL OIL SUPPLY FLUID PRESSURE DROP FEET PER MINUTE
FS FT	FLOW SWITCH FEET/FOOT
FV G	FACE VELOCITY GAS
GA GAL	GAUGE GALLON
GALV GPH	GALVANIZED GALLONS PER HOUR
GPM GR	GALLONS PER MINUTE GRADE
H HC	HEIGHT/HIGH/HUMIDITY SENSOR HEATING COIL
LID	HEAD HAND-OFF-AUTOMATIC SWITCH HIGH PRESSURE/HORSEPOWER
HOA	THE STATE OF THE SECTION OF THE SECT
HOA HP HR	HEATING RETURN/HOUR
HOA HP HR HS HTG	HEATING RETURN/HOUR HEATING SUPPLY/HIGH SCHOOL HEATING
HOA HP HR HS	HEATING RETURN/HOUR HEATING SUPPLY/HIGH SCHOOL

ABBREV	DESCRIPTION
IN INSUL	INCH/INCHES INSULATION/INSULATED
INT	INTERIOR
INV	INVERT
IPLV IPS	INTEGRATED PART LOAD VALUE IRON PIPE SIZE
IT TVA/	INFORMATION TECHNOLOGY
IW KW	INDIRECT WASTE KILOWATT
L	LENGTH
LAT LFT	LEAVING AIR TEMPERATURE LEAVING FLUID TEMPERATURE
LRA	LOCKED ROTOR AMPS
LWT	LEAVING WATER TEMPERATURE
M MAX	MECHANICAL MAXIMUM
MBH	THOUSAND BTU PER HOUR
MCA MCC	MINIMUM CIRCUIT AMPS MOTOR CONTROL CENTER
MECH	MECHANICAL
MER MIN	MECHANICAL EQUIPMENT ROOM MINIMUM
MISC	MISCELLANEOUS
MOCP	MAXIMUM OVERCURRENT PROTECTION
MOD MTD	MOTOR-OPERATED DAMPER MOUNTED
MTG	MOUNTING
MV N	MIXING VALVE NORTH
N/A	NOT APPLICIBLE
NC NIC	NOISE CRITERIA/NORMALLY CLOSED NOT IN CONTRACT
NIC NO	NOT IN CONTRACT NORMALLY OPEN/NUMBER
NOM	NOMINAL
NPLV NPSH	NON-STANDARD PART LOAD VALUE NET POSITIVE SUCTION HEAD
NPSHA	NET POSITIVE SUCTION HEAD AVAILABLE
NPSHR	NET POSITIVE SUCTION HEAD REQUIRED
NPW NTS	NON-POTABLE WATER NOT TO SCALE
OA	OUTDOOR AIR
OC OED	ON CENTER OPEN-END DUCT
ОН	OVERHEAD
OPER OPP	OPERATING/OPERATOR OPPOSITE
P	PIPE/PLUMBING FIXTURE TYPE/PRESSURE
PD	PRESSURE DROP/PUMP DISCHARGE
PH PHC	PHASE PREHEAT COIL
PL	PLATE/PILOT LIGHT
PPM	PARTS PER MILLION
PRV PSF	PRESSURE REDUCING VALVE POUNDS PER SQUARE FOOT
PSI	PRESSURE-POUNDS PER SQUARE INCH
PSIG PVC	PRESSURE-POUNDS PER SQUARE INCH, GAGE POLYVINYL CHLORIDE
R	REGISTER/RISE
RA	RETURN AIR
RAD RAF	RADIUS RETURN AIR FAN
REFRIG	REFRIGERANT/REFRIGERATION
REG REQD	REGISTER/REGULATOR REQUIRED
RET	RETURN
RH	REHEAT/RELATIVE HUMIDITY
RHC RL	REHEAT COIL REFRIGERANT LIQUID
RLA	RUNNING LOAD AMPS
RM ROCP	ROOM RECOMMENDED OVERCURRENT PROTECTION
RPBP	REDUCED PRESSURE BACKFLOW PREVENTOR
RPM DC	REVOLUTIONS PER MINUTE REFRIGERANT SENSOR/REFRIGERANT SUCTION
RS RTU	REFRIGERANT SENSOR/REFRIGERANT SUCTION ROOFTOP UNIT
RV	RELIEF VALVE
RX	REMOVE EXISTING
S SA	SOUTH/SWITCH/SUCTION SOUND ATTENUATOR/SUPPLY AIR
SAN	SANITARY
SD	SMOKE DAMPER/SMOKE DETECTOR
SEER SENS	SEASONAL ENERGY EFFICIENCY RATIO SENSIBLE COOLING
SF	SQUARE FEET/SQUARE FOOT
SH SHGC	SHOWER SOLAR HEAT GAIN COEFFICIENT
SHR	SENSIBLE HEAT RATIO
SP SQ	SPRINKLER PIPING/STATIC PRESSURE SENSOR
SS	SQUARE SERVICE SINK/STAINLESS STEEL
SST	SATURATION SUCTION TEMPERATURE
STD STL	STANDARD STEEL
SW	STORM WATER
T TAO	TEMPERATURE SENSOR TRANSFER AIR OPENING
TEMP	TEMPERATURE/TEMPORARY
TOT	TOTAL
TP TSP	TOTAL PRESSURE TOTAL STATIC PRESSURE
TYP	TYPICAL
UH UTE	UNIT HEATER UNEQUAL THROAT ELBOW
UV	ULTRA VIOLET/UNIT VENTILATOR
V	VACUUM/VALVE/VENT/VOLTS
VAV VD	VARIABLE AIR VOLUME VOLUME DAMPER
VEL	VELOCITY
VERT VFD	VERTICAL VARIABLE FREQUENCY DRIVE
VFD VOL	VOLUME VOLUME
VSD	VARIABLE SPEED DRIVE
WB	WET BULB

MECH	ANICAL ABBREVIATIONS
ABBREV	DESCRIPTION
IN	INCH/INCHES
INSUL INT	INSULATION/INSULATED INTERIOR
INV	INVERT
IPLV IPS	INTEGRATED PART LOAD VALUE IRON PIPE SIZE
IT	INFORMATION TECHNOLOGY
IW KW	INDIRECT WASTE KILOWATT
L	LENGTH
LAT LFT	LEAVING AIR TEMPERATURE LEAVING FLUID TEMPERATURE
LRA	LOCKED ROTOR AMPS
LWT M	LEAVING WATER TEMPERATURE MECHANICAL
MAX	MAXIMUM THOUGAND BY LIBER HOLER
MBH MCA	THOUSAND BTU PER HOUR MINIMUM CIRCUIT AMPS
MCC	MOTOR CONTROL CENTER
MECH MER	MECHANICAL MECHANICAL EQUIPMENT ROOM
MIN	MINIMUM
MISC MOCP	MISCELLANEOUS MAXIMUM OVERCURRENT PROTECTION
MOD	MOTOR-OPERATED DAMPER
MTD MTG	MOUNTED MOUNTING
MV	MIXING VALVE
N/A	NORTH NOT APPLICIBLE
NC	NOISE CRITERIA/NORMALLY CLOSED
NIC NO	NOT IN CONTRACT NORMALLY OPEN/NUMBER
NOM	NOMINAL NON CTANDARD PART LOAD VALUE
NPLV NPSH	NON-STANDARD PART LOAD VALUE NET POSITIVE SUCTION HEAD
NPSHA	NET POSITIVE SUCTION HEAD AVAILABLE
NPSHR NPW	NET POSITIVE SUCTION HEAD REQUIRED NON-POTABLE WATER
NTS	NOT TO SCALE
OA OC	OUTDOOR AIR ON CENTER
OED	OPEN-END DUCT
OH OPER	OVERHEAD OPERATING/OPERATOR
OPP	OPPOSITE
P PD	PIPE/PLUMBING FIXTURE TYPE/PRESSURE PRESSURE DROP/PUMP DISCHARGE
PH	PHASE
PHC PL	PREHEAT COIL PLATE/PILOT LIGHT
PPM	PARTS PER MILLION
PRV PSF	PRESSURE REDUCING VALVE POUNDS PER SQUARE FOOT
PSI	PRESSURE-POUNDS PER SQUARE INCH
PSIG PVC	PRESSURE-POUNDS PER SQUARE INCH, GAGE POLYVINYL CHLORIDE
R	REGISTER/RISE
RA	RETURN AIR
RAD RAF	RADIUS RETURN AIR FAN
REFRIG	REFRIGERANT/REFRIGERATION
REG REQD	REGISTER/REGULATOR REQUIRED
RET	RETURN
RH RHC	REHEAT/RELATIVE HUMIDITY REHEAT COIL
RL	REFRIGERANT LIQUID
RLA RM	RUNNING LOAD AMPS ROOM
ROCP	RECOMMENDED OVERCURRENT PROTECTION
RPBP RPM	REDUCED PRESSURE BACKFLOW PREVENTOR REVOLUTIONS PER MINUTE
RS	REFRIGERANT SENSOR/REFRIGERANT SUCTION
RTU	ROOFTOP UNIT RELIEF VALVE
RV RX	REMOVE EXISTING
S	SOUTH/SWITCH/SUCTION
SA SAN	SOUND ATTENUATOR/SUPPLY AIR SANITARY
SD	SMOKE DAMPER/SMOKE DETECTOR
SEER SENS	SEASONAL ENERGY EFFICIENCY RATIO SENSIBLE COOLING
SF	SQUARE FEET/SQUARE FOOT
SH SHGC	SHOWER SOLAR HEAT GAIN COEFFICIENT
SHR	SENSIBLE HEAT RATIO
SP SQ	SPRINKLER PIPING/STATIC PRESSURE SENSOR SQUARE
SS	SERVICE SINK/STAINLESS STEEL
SST STD	SATURATION SUCTION TEMPERATURE STANDARD
STL	STEEL
SW T	STORM WATER TEMPERATURE SENSOR
TAO	TRANSFER AIR OPENING

Gipe Associates In Consulting Engineers DESIGNER

WO# 22082

100% IAC SUBMISSION 03/24/2023

PUMP SCHEDULE										
UNIT	AREA SERVED	GPM	FT OF		МОТОІ	R	EFFICIENCY	SIZE (SxD)	REMARKS	BASED ON
P-X	ARLA SERVED	Griff	HEAD	HP	RPM	V/ø/Hz	%	312L (3XD)	KENAKO	(TACO)
P-4	PRIMARY CHILLED WATER	875	40	20	1760	460/3/60	82	5x6x9.5	SPLIT CASE	TACO TA1224
	PRIMARY CHILLED WATER (SB)	875	40	20	1760	460/3/60	82	5x6x9.5	SPLIT CASE	TACO TA122
P-6	PRIMARY CHILLED WATER	875	40	20	1760	460/3/60	82	5x6x9.5	SPLIT CASE	TACO TA122
P-7	SECONDARY CHILLED WATER	870	110	40	1760	460/3/60	78	5x6x12	SPLIT CASE	TACO TA123
P-8	SECONDARY CHILLED WATER	870	110	40	1760	460/3/60	78	5x6x12	SPLIT CASE	TACO TA123

1. PROVIDE VARIABLE SPEED DRIVES AND INVERTED DUTY MOTORS FOR PUMPS.

2. SB = STANDBY SERVICE.

								AIR-C	COOLE	D C	HILL	ER SC	HED	ULI	E						
							PERFORMANO			RMANCE	SINGLE POINT ELECTRICAL										
CHILLER Nº	TONS	MAX KW	No. OF COMP.	REFRIG. TYPE	TYPE FLUID EFT (°F) LFT (°F) GPM No. of PASSES MAX.	MAX. FPD	EAT (°F)	EER (FL)	MAX IPLV (BTU/Wh)	RLA	LRA	МСА	МОСР	V	РН	Hz	KS	BASIS OF DESIGN			
1	400	468	2	R-513A	WATER	53 42	2 899.1	2	18.4	95.0	10.3	18.9	-	-	842	1000	460	3	60 1, 2, 3,	4	Carrier 30XV450S
2	400	468	2	R-513A	WATER	53 42	2 899.1	2	18.4	95.0	10.3	18.9	-	-	842	1000	480	3	60 1, 2, 3,	4	Carrier 30XV450S


1. COMP 1: 14.7A RLA; COMP 2: 14.7A RLA; COMP 3: 165A RLA. 2. EACH CONDENSER FAN: 2.8A FLA.

3. UNIT STARTERS SHALL BE VSD.

4. CHILLER WEIGHT: 27500 LBS



- 1 REMOVE EXISTING PUMPS P-7 & P-8 AT PIPE CONNECTION.
- REMOVE EXISTING PUMPS P-4, P-5, & P-6 AT PIPE CONNECTION.







Gipe Associates Inc Consulting Engineers

WO# 22082

07.042.23





100% IAC SUBMISSION 03/24/2023 SCALE: 1/4" = 1'-0"

M1.2

THIS DRAV CONSTRUC ARE PROP ASSOCIAT ALTERED (PART WITH PERMISSIC Copyright ©

Gipe Associates Inc.
Consulting Engineers

1220 East Joppa Road
Suite 223
Towson, MD. 21286
Phone: 410/832-2420
Fax: 410/832-2418


Gipe 2-5
Easton, Maryland 21601
Phone: 410/832-2420
Fax: 410/832-2418

WO# 22082

07.042.23

PROJECT MANAGER

DESIGNER





EX BOILER TO REMAIN

EX BOILER TO REMAIN

MATCHLINE - REFER TO DRAWING M2.2 FOR CONTINUATION


FD

EX ATC COMPRESSOR

EX BLOW DOWN TANK

EX AUX CONDENSATE TANK

EX DEAERATOR






WO# 22082

MECHANICAL ROOM PART PLAN - NEW WORK CECIL SCHOOL OF TECHNOLOGY CHILLER REPLACEMENT CECIL COUNTY PUBLIC SCHOOLS

100% IAC SUBMISSION 03/24/2023

M2.1



SCALE: 1/4" = 1'-0"

Gipe Associates Inc.
Consulting Engineers


1220 East Joppa Road
Suite 223
Towson, MD. 21286
Fax: 410/832-2420
Fax: 410/832-2418


Gipe Associates Inc.
Suite 2-5
Easton, Maryland 21601
Phone: 410/832-2420
Fax: 410/822-6306 DESIGNER


WO# 22082

07.042.23

THIS I CONS ARE F ASSO ALTEF PART PERM CODYI







	CAL LEGEND
	GHTS ARE TO CENTERLINE OF WALL MOUNTED DEVICES AND TO THE HTING FIXTURES UNLESS OTHERWISE NOTED.)
	POWER
	PANELBOARD - SURFACE, RECESSED MOUNTED, M.H. 6'-6" AFF TO TOP OF PANEL
(E) (□	SAFETY SWITCH, FUSED OR NON-FUSED, SIZE AS INDICATED ON DRAWINGS. ENCLOSURE SHALL BE NEMA 1 UNLESS OTHERWISE NOTED, MOUNT 5'-6" AFF TO TOP UNLESS OTHERWISE NOTED
4	STARTER, COMBINATION STARTER FVNR TYPE NEMA SIZE 1 UNLESS OTHERWISE NOTED, WITH NON-FUSED DISCONNECT SWITCH, H.O.A. SELECTOR SWITCH, RED & GREEN INDICATING LIGHTS AND CONTROL POWER TRANSFORMER IN NEMA 1 ENCLOSURE UON, M.H. 5'-6" AFF TO TOP.
<i>/</i> /	MOTOR
0	JUNCTION BOX - CEILING, WALL MOUNTED
숙	EMERGENCY POWER OFF BUTTON
C#	CONTACTOR; SIZE AS NOTED; IN NEMA 1 ENCLOSURE UON; MOUNT AT 5'-6" AFF TO TOP UON
Ś™	1P, 20A MANUAL MOTOR STARTER
무	UNIT HEATER
VFD	VARIABLE FREQUENCY DRIVE (FURNISHED UNDER DIVISION 23), INSTALLED UNDER DIVISION 26
FM	FLOW METER
<u>GF</u>	GROUND FAULT PROTECTION
ERMS	ENERGY REDUCTION MAINTENANCE SWITCH
	OUTLETS DUDI EN RECERTACIE OR ON ORA 12EN MEMA E 200 MOUNT 11 CII AEE HON
Φ	DUPLEX RECEPTACLE; 2P, 3W, 20A, 125V, NEMA 5-20R; MOUNT 1'-6" AFF UON. DOUBLE DUPLEX RECEPTACLE; 2P, 3W, 20A, 125V, NEMA 5-20R; MOUNT 1'-6"
 	AFF UON.
Φ	DUPLEX RECEPTACLE; 2P, 3W, 20A, 125V, NEMA 5-20R; GROUND FAULT INTERRUPTING WITH WEATHERPROOF COVER. MOUNT AT 1'-6" AFF UON.
	TELECOMMUNICATIONS
S S	SPEAKER; CEILING MOUNTED, WALL MOUNTED AT 7'-6" AFF UON
a q	WP - WEATHERRESISTANT, H - HORN TYPE
	LIGHTING
	SUSPENDED LIGHT FIXTURE
⊗	EXIT SIGN
4	EMERGENCY WALL PACK
\$ \$ ³ \$ ⁴	SWITCH; SINGLE LOAD, 3-WAY, 4-WAY; SUBSCRIPT INDICATES FIXTURES/OUTLETS CONTROLLED; MOUNT AT 4'-0" AFF TO TOP
	FIRE ALARM
	FIRE ALARM ANNUNCIATOR/FIRE ALARM CONTROL PANEL AS NOTED, MOUNT 56" AFF TO TOP
F	FIRE ALARM PULL STATION; MOUNT AT 4'-0" AFF TO TOP
- \Z -	WALL MOUNTED FIRE ALARM HORN/STROBE LIGHT; CANDELA RATING AS INDICATED; WALL MOUNTED 80" AFF TO TOP OR 12" BELOW CEILING, WHICHEVER IS LOWER.
	CONDUIT
	HOMERUN TO PANELBOARD; NUMBER OF ARROWHEADS INDICATE NUMBER OF CIRCUITS; REFER TO PANEL SCHEDULES FOR MINIMUM WIRE AND CONDUIT
	SIZES CONDUIT OR WIRE CONCEALED IN CEILING SPACE, WALL OR SURFACE
	MOUNTED WHERE NO CEILING EXISTS
	CONDUIT OR WIRE ROUTED IN OR BELOW FLOOR SLAB.
	MISCELLANEOUS
	DENOTES REFERENCE TO DRAWING NOTE ITEMS SHOWN SOLID AND LIGHT ARE EXISTING TO REMAIN.
	ITEMS SHOWN SOLID AND LIGHT ARE EXISTING TO REMAIN. ITEMS SHOWN DARK AND DASHED ARE TO BE REMOVED. REMOVE ALL
	ASSOCIATED ELECTRICAL WORK BACK TO SOURCE UNLESS OTHERWISE NOTED.
	ITEMS SHOWN DARK AND SOLID ARE NEW.

GENERAL NOTES:

- THE ELECTRICAL CONTRACTOR SHALL FAMILIARIZE HIMSELF WITH THE DRAWINGS OF ALL OTHER TRADES ON THE PROJECT. ELECTRICAL OR SYSTEMS CONNECTIONS INDICATED ON MECHANICAL DRAWINGS WHICH ARE PART OF THIS PROJECT, SHALL BE CONSIDERED A PART OF THIS CONTRACT AND SHALL BE PROVIDED BY THE ELECTRICAL CONTRACTOR AT NO EXTRA COST TO THE OWNER.
- 2. THE ELECTRICAL DRAWINGS ARE DIAGRAMMATIC IN NATURE AND AS SUCH SHALL NOT BE SCALED. REFER TO THE ARCHITECTURAL DRAWINGS FOR EXACT LOCATIONS OF DEVICES AND EQUIPMENT AND DIMENSIONAL INFORMATION PRIOR TO ROUGH-IN. COORDINATE LOCATIONS OF MECHANICAL EQUIPMENT WITH MECHANICAL CONTRACTOR PRIOR TO ROUGH-IN OF SERVICE EQUIPMENT AND WIRING.
- 3. THE CONTRACTOR SHALL BE RESPONSIBLE FOR DETERMINING THE EXACT ROUTING OF WIRING AND CONDUITS AND SHALL BE RESPONSIBLE FOR SIZING ALL BRANCH CIRCUIT WIRING TO LIMIT VOLTAGE DROP TO 3%. CONTRACTOR SHALL SIZE CONDUIT TO ACCOMMODATE WIRING PER NEC. 20 AMPERE CIRCUITS SHALL BE SIZED AS FOLLOWS:

	20 /	AMPERE CIRCUITS		
120 VOL	.Т	277 VOL	Т	MINIMUM
WIRING LENGTH	WIRE SIZE	WIRING LENGTH	WIRE SIZE	CONDUIT SIZE
0' - 60'	#12	0' - 130'	#12	3/4"
60' - 100'	#10	130' - 210'	#10	3/4"
100' - 150'	#8	210' - 340'	#8	3/4"
150' - 240'	#6	340' - 540'	#6	3/4"
OVER 240'	#4	OVER 540'	#4	1"
NOTES	•		•	

BRANCH CIRCUITS IN PANELBOARDS WITH 200% RATED NEUTRAL BUS, ECM MOTORS AND ALL DIMMED LIGHTING CIRCUITS SHALL HAVE DEDICATED NEUTRAL CONDUCTORS.

BE RESPONSIBLE FOR DETERMINING EXACT WIRING AND CONDUIT SIZES. CONTRACTOR SHALL PROVIDE SPLICE BLOCKS AND REDUCING PINS AS REQUIRED TO TERMINATE WIRING AND MAKE FINAL CONNECTIONS.

4. REMOVE AND REINSTALL EX SUSPENDED LIGHT FIXTURES AS REQUIRED TO ACCOMODATE NEW MECHANICAL WORK. ADJUST FIXTURE HEIGHT AND/OR LOCATION(S) AS REQUIRED TO SUIT NEW CONFIGURATION,

WIRING AND CONDUIT SIZES INDICATED IN PANEL SCHEDULES ARE MINIMUM ONLY. CONTRACTOR SHALL

5. NEW CIRCUITS CONNECTED TO EXISTING CIRCUIT BREAKERS ARE INDICATED IN EXISTING PANELS (SHOWN BOLD IN SCHEDULE)

BOLD IN SCHEDULE).

DEMOLITION NOTES

EXTEND ASSOCIATED CONDUIT AND WIRE AS REQUIRED.

- DEMOLITION DRAWING IS DIAGRAMMATIC IN NATURE; NO ATTEMPT HAS BEEN MADE TO SHOW ALL EXISTING ELECTRICAL WORK. IN AREAS INDICATED TO BE RENOVATED. ALL EXISTING ELECTRICAL WORK SHALL REMAIN UNLESS OTHERWISE NOTED. WHEN AN ITEM IS INDICATED TO BE REMOVED, REMOVE ALL ASSOCIATED ELECTRICAL WORK BACK TO POINT OF SOURCE UON.
- 2. WHERE WORK PASSES THROUGH THE RENOVATION AREA TO SERVE OTHER PORTIONS OF THE BUILDING, OR WORK IN THE RENOVATION AREA INDICATED TO REMAIN, IT SHALL BE SUITABLY RELOCATED AND THE SYSTEMS RESTORED TO NORMAL, COORDINATE ANY OUTAGES WITH OWNER 15 DAYS IN ADVANCE.
- 3. WORK INDICATED TO REMAIN SHALL BE SUITABLY PROTECTED AGAINST DAMAGE.
- 4. DISCONNECT AND REMOVE ALL ELECTRICAL WORK ASSOCIATED WITH MECHANICAL EQUIPMENT INDICATED TO BE REMOVED UNDER DIVISION 23, UON.


ABBREVIATIONS

ABBREV	'IATIONS
A	AMPERE, AMPERES
AFF	ABOVE FINISHED FLOOR
AFG	ABOVE FINISHED GRADE
AHU	AIR HANDLING UNIT
AHJ	AUTHORITY HAVING JURISDICTION
AIC	AMPERE INTERRUPTING CAPACITY
AL	ALUMINUM
AWG	AMERICAN WIRE GAUGE
C	CONDUIT
CB	CIRCUIT BREAKER
CLG	CEILING, CEILING MOUNTED
DIA	DIAMETER
DWG E	DRAWING EMERICAL
EC	EMERGENCY ELECTRICAL CONTRACTOR
ECB	ENCLOSED CIRCUIT BREAKER
EF	EXHAUST FAN
EMCS	ENERGY MANAGEMENT CONTROL SYSTEM
Lines	EMERGENCY POWER OFF
EPO	EXISTING TO REMAIN
ETR	EXISTING TO KEMAIN
EX	FIRE ALARM
FA	FIRE ALARM ANNUNCIATOR PANEL
FAAP	FIRE ALARM CONTROL PANEL
FACP	FULL LOAD AMPERES
FLA	FUSED SAFETY SWITCH
FSS	GROUND FAULT INTERRUPTING
GFI	GROUND
G	GROUND WIRE
GW	HIGH
H HOA	HAND-OFF-AUTOMATIC
HP	HORSEPOWER
IMC	INTERMEDIATE METAL CONDUIT
KCMIL	THOUSAND CIRCULAR MILS
KVA	KILOVOLT-AMPERES
KW	KILOWATT
L	LOW
LRA MCA	LOCKED ROTOR AMPERES
MCB	MINIMUM CIRCUIT AMPERES
MLO	MAIN CIRCUIT BREAKER
MOCP	MAIN LUGS ONLY
MTD	MAXIMUM OVERCURRENT PROTECTION
MH	MOUNTED
NEC	MOUNTING HEIGHT/MANHOLE NATIONAL ELECTRICAL CODE
NEMA	NATIONAL ELECTRICAL CODE NATIONAL ELECTRICAL MANUFACTURERS
	ASSOCIATION
NF/SS	NONFUSED SAFETY SWITCH
NIC	NOT IN CONTRACT
NO	NUMBER
OC	ON CENTERS
Р	POLE, POLES
Φ	PHASE
PNL	PANEL
PVC	POLYVINYL CHLORIDE
RAF	RETURN AIR FAN
RGS	RIGID GALVANIZED STEEL
RX TAP	REMOVE EXISTING
TR	TAP SECTION
TYP	TAMPER RESISTANT
UH	TYPICAL
V	UNIT HEATER
VR	VOLT, VOLTS
WP	VANDAL RESISTANT WEATHERPROOF
W	WATTS, WIRE, WIRES
XFMR	TRANSFORMER
TTB	TELEPHONE TERMINAL BOARD
UON	UNLESS OTHERWISE NOTED
	C.LEGO OTTENTIGE NOTED

DATE DESCRIPTION

PROFESSIONAL CERTIFICATION:

I HEREBY CERTIFY THAT THESE
DOCUMENTS WERE PREPARED OR
APPROVED BY ME, AND THAT I AM A
DULY LICENSED PROFESSIONAL
ENGINEER UNDER THE LAWS OF THE
STATE OF MARYLAND, LICENSE NO.



THIS DRAWING AND THE DESIGN AND CONSTRUCTION FEATURES DISCLOSED ARE PROPRIETARY TO GIPE ASSOCIATES, INC. AND SHALL NOT BE ALTERED OR REUSED IN WHOLE OR IN PART WITHOUT THE EXPRESS WRITTEN PERMISSION OF GIPE ASSOCIATES, INC. Copyright © 2023

Gipe Associates Inc.
Consulting Engineers

1220 East Joppa Road Suite 223
Towson, MD. 21286 Easton, Maryland 21601
Phone: 410/832-2420
Fax: 410/832-2418

Fax: 410/832-2418

YO# 22082

PROJECT KTC

MANAGER KTC

DESIGNER KTC


PSC#: 07


PSC#: 07

LEGEND, SCHEDULES & ABBREVIATIONS
CECIL SCHOOL OF TECHNOLOGY CHILLER REPLACEMENT
CECIL COUNTY PUBLIC SCHOOLS

100% IAC SUBMISSION 03/24/2023

E0.0






GENERAL NOTES: REFER TO PANEL SCHEDULES AND MECHANICAL EQUIPMENT CONNECTION SCHEDULE ON DRAWING E5.1 FOR ADDITIONAL INFORMATION. 2. CUT AND PATCH EXISTING FLOORS AS REQUIRED TO INSTALL GROUNDING. **DRAWING NOTES:** PROVIDE 2 #12 AND 1 #12 GROUND IN 3/4" CONDUIT AS REQUIRED AND MAKE ALL CONNECTIONS TO NEAREST EXTERIOR RECEPTACLE. THIS I CONS ARE F ASSO ALTEF PART PERM CODYI CHILLER-1 Gipe Associates Inc.
Consulting Engineers

1220 East Joppa Road Suite 223
Towson, MD. 21286 Easton, Maryland 21601 Phone: 410/832-2420 Fax: 410/832-2418 CONTROL PANEL WO# 22082 CHILLER-2 DESIGNER 07.042.23 CONTROL PANEL MATCHLINE - REFER TO DRAWING E2.1 FOR CONTINUATION COURTYARD PART PLAN - ELECTRICAL NEW WORK

SCALE: 1/4" = 1'-0"

E2.2



PARTIAL SINGLE LINE DIAGRAM - DEMOLITION



THIS I CONS ARE F ASSO ALTER PART PERM COPYI

Gipe Associates Inc.
Consulting Engineers


1220 East Joppa Road
Suite 223
Towson, MD. 21286
Phone: 410/832-2420
Fax: 410/832-2418

Gipe 2-5
Easton, Maryland 21601
Phone: 410/832-2420
Fax: 410/832-2418

WO# 22082 PROJECT MANAGER KTC KTC DESIGNER

07.042.23

PARTIAL SINGELINE DIAGRAM - DEMOLITION
CECIL SCHOOL OF TECHNOLOGY CHILLER REPLACEMENT
CECIL COUNTY PUBLIC SCHOOLS



DRAWING NOTES:

GENERAL NOTES:

1. REFER TO PANEL SCHEDULES FOR ADDITIONAL INFORMATION.

2. CONTRACTOR SHALL REDUCE FEEDER SIZE (IF REQUIRED) WITHIN 5'-0" OF EQUIPMENT TO ACCOMMODATE LUG SIZES.

1 UTILIZE EXISTING CONDUIT FOR ROUTING OF NEW FEEDER AND EXTEND AS REQUIRED. 2) 3# 3/0 ERP (5KV SHIELDED), 133% INSULATION COPPER CABLE, 1 #4 600V INSULATED GROUND.

3 SETS (3#300KCMIL + 2/0GW IN 3" CONDUIT).



THIS I CONS ARE F ASSO ALTER PART PERM COPYI

Gipe Associates Inc.
Consulting Engineers

1220 East Joppa Road
Suite 2.23
Towson, MD. 21286
Phone: 410/832-2420
Fax: 410/832-2418


Gipe 2-5
Easton, Maryland 21601
Phone: 410/832-2420
Fax: 410/832-2418

WO# 22082 PROJECT MANAGER KTC KTC DESIGNER

07.042.23

PARTIAL SINGE LINE DIAGRAM - NEW WORK
CECIL SCHOOL OF TECHNOLOGY CHILLER REPLACEMENT
CECIL COUNTY PUBLIC SCHOOLS

100% IAC SUBMISSION



MOL	INTING: FREE STANDING	A.I.C. RA	TING:	12,000					LOCATION: CUP COURTYARD		
VOL	TAGE: 4160, 3PHASE, 3 WIRE		1200 AM	PERE M	IAIN BU	S				1200 AMPERE MAIN CIRCUIT BRE	AKER
			DISTRIE	BUTIO	N SEC	ΓΙΟΝ					
FDR			CON								
NO	SERVES	Р	FRAME	TRIP	SETS	NO	SIZE	GND	С	REMARKS	KVA
1	EX SUBSTATION 1	3	600	400E							
2	EX SUBSTATION 2	3	600	400E							
3	EX CHILLER 1 AND CHILLER 2	3	600	150E							
4	EX SUBSTATION 3	3	600	150E							
5	FUTURE BUILDING										
6	FUTURE BUILDING										
7	FUTURE CHILLERS										

MOL	INTING: FREE STANDING		A.I.C. RA	ATING:	12,000			LOCATION: CUP COURTYARD			
VOL	TAGE: 4160, 3PHASE, 3 WIRE		1200 AM	PERE N	IAIN BU	s				1200 AMPERE MAIN CIRCUIT BREAKER	
			DISTRIE	BUTIO	N SEC	ΓΙΟΝ					
FDR		CIF	CUIT BR	EAKER			WIRING				CONN
NO	SERVES	Р	FRAME	TRIP	SETS	NO	SIZE	GND	С	REMARKS	KVA
1	EX SUBSTATION 1	3	600	400E							
2	EX SUBSTATION 2	3	600	400E							
3	SUBSTATION CHILLER	3	600	250E	REF	ER TO	ONLINE	DIAGRA	AM	MODIFY SWITCH AS REQUIRED	
4	EX SUBSTATION 3	3	600	150E							
5	FUTURE BUILDING										
6	FUTURE BUILDING										
7	FUTURE CHILLERS										

	TAGE: 480, 3PH, 3W ATION: MECH RM 208			HORIZONTAL BUS: 800A VERTICAL BUS: 800A									A.I.C. RATING: 42,000 800 AMPERE MAIN LUGS ONLY				
CKT				CIRCUIT BREAKER					W	/IRING		STARTER				CON	
NO	SERVES	HP	KW	Р	FRAME	TRIP	SETS	NO	SIZE	GND	С	SIZE	TYPE	AUX	REMARKS	KVA	
A1	SPARE			3	100							X					
A2	EX P-7 (CHW SEC.)			3	100	100											
А3	EX B-1			3	100	70											
A4	EX D-1			3	100	30											
A5	EX ATC-2			3	100	20											
A6	EX DWBP-2			3	100	20											
B1	EX P-6 (CHW PRI)			3	100	30						Х					
B2	EX SF-11			3	100	100						Х					
ВЗ	EX EF-12			3	100	100						Х					
B4	EX EF-13			3	100	15						Х					
B5	EX P-8 (CHW SEC)			3	100	15											
C1	EX CT-1			3	100	50						Х					
C2	EX MOTORIZED DOOR			3	100	15						Х					
D1	EX CT-2			3	100	50						Х					
D2	EX P-1 (CDW)			3	100	70						Х					
E1	EX P-2 (CDW)			3	100	70						Х					
E2	EX P-3 (CDW)			3	100	70						Х					
E3	EX P-4 (CHW PRI)			3	100	30						Х					
E4	EX P-5 (CHW PRI)			3	100	30						Х					
E5	SPARE			3	100												
F1	EX EF-14			3	100	15						Х					
F2	EX SF-9			3	100	15						Х					
F3	EX SF-10			3	100	15						Х					
F4	SPARE			3	100							X					
F5	SPARE			3	100							X					
F6	SPARE			3	100							Х					

VOL	TAGE: 480, 3PH, 3W	HORIZONTAL BUS: 800A											A.I.C. RATING: 42,000			
LOC	ATION: MECH RM 208		VERTICA	L BUS:	A008					800 AMPERE MAIN LUGS ONL						
CKT					CIRCUI	T BREAKER		WIRING					STARTER			CON
NO	SERVES	HP	KW	Р	FRAME	TRIP	SETS	NO	SIZE	GND	С	SIZE	TYPE	AUX	REMARKS	KVA
A1	SPARE			3	100							Х				
A2	PUMP-7			3	100	100	1	3	6	8	1-1/4				NOTE 2	41.0
А3	EX B-1			3	100	70										
A4	EX D-1			3	100	30										
A5	EX ATC-2			3	100	20										
A6	EX DWBP-2			3	100	20										
B1	SPARE			3	100	30						Х				
B2	EX SF-11			3	100	100						Х				
В3	EX EF-12			3	100	100						Х				
B4	EX EF-13			3	100	15						Х				
B5	PUMP-8			3	100	100	1	3	6	8	1-1/4					41.0
C1	EX CT-1			3	100	50						Х				
C2	EX MOTORIZED DOOR			3	100	15						Х				
D1	EX CT-2			3	100	50						Х				
D2	PUMP-4			3	100	60	1	3	8	10	3/4	Х			NOTE 2	21.3
E1	PUMP-5 (STAND-BY)			3	100	60	1	3	8	10	3/4	Х			NOTE 2	
E2	PUMP-6			3	100	60	1	3	8	10	3/4	Х			NOTE 2	21.3
E3	SPARE			3	100	30						Х				
E4	SPARE			3	100	30						Х				
E5	SPARE			3	100											
F1	EX EF-14			3	100	15						Х				
F2	EX SF-9			3	100	15						Х				
F3	EX SF-10			3	100	15						Х				
F4	SPARE			3	100							Х				
F5	SPARE			3	100							Х				
F6	SPARE			3	100							Х				
	R STARTER AUXILIARY DEVICES 120 VOLT CONTROL POWER TRAI	NSFORM	IER	3	100							T TO P			BREAKER.	RCL

TOTAL CONNECTED LOAD IN KVA: 0

TOTAL CONNECTED LOAD IN KVA: 124.6

GENERAL NOTES:

C GREEN "OFF" INDICATING LIGHT

D HAND-OFF-AUTOMATIC SELECTOR SWITCH E 2-NO, 2-NC AUXILIARY CONTACTS

A 120 VOLT CONTROL POWER TRANSFORMER

D HAND-OFF-AUTOMATIC SELECTOR SWITCH

B RED "ON" INDICATEING LIGHT C GREEN "OFF" INDICATING LIGHT

E 2-NO, 2-NC AUXILIARY CONTACTS

1. PROVIDE NEW CIRCUIT BREAKERS IN EXISTING TO REMAIN PANELS (SHOWN BOLD IN SCHEDULE).
NEW CIRCUIT BREAKER SHALL MATCH EXISTING MANUFACTURER, STYLE, TYPE AND SHORT CIRCUIT RATING.

			SER	VICE	CIRCUIT	NEMA						
EQUIPMENT	KW	HP	AMPS	VOLTS	PH	DESIGNATION	SIZE STARTER	POLE	AMPS	FUSE VERIFY W/ NAMEPLATE	NEMA ENCLOSURE	NOTES
CHILLER-1			842.1	480	3	SS-CH-1		3	1200	1000	NEMA 3R	1
CHILLER-2			842.1	480	3	SS-CH-2		3	1200	1000	NEMA 3R	1
P-4		20		480	3	MCC-D2						3
P-5 (STAND-BY)		20		480	3	MCC-E1						3
P-6		20		480	3	MCC-E2						3
P-7		40		480	3	MCC-A2						3
P-8		40		480	3	MCC-B5						3

MECHANICAL SCHEDULE NOTES:

1. SINGLE POINT CONNECTION. MAKE ALL CONNECTIONS TO UNIT AS REQUIRED

2. PROVIDE COMBINATION TYPE MOTOR STARTER FVNR WITH CONTROL TRANSFORMER, RED AND GREEN INDICATING LIGHTS, AND DISCONNECT.

3. INSTALL VFD (FURNISHED UNDER MECHANICAL DIVISION) MAKE ALL CONNECTIONS TO MOTOR AS REQUIRED

4. MAKE CONNECTION TO CONTROL PANEL FURNISHED WITH UNIT.



THIS I CONS ARE F ASSO ALTEF PART PERM COPYII

Gipe Associates Inc.
Consulting Engineers

1220 East Joppa Road
Suite 2.3
Towson, MD. 21286
Phone: 410/832-2420
Fax: 410/832-2418

Gipe 2-5
Easton, Maryland 21601
Phone: 410/832-2420
Fax: 410/832-2418

WO# 22082 Project Manager KTC

KTC DESIGNER

07.042.23

MECHANICAL EQUIPMENT CONNECTION AND PANELBOARD SCHEDUL CECIL SCHOOL OF TECHNOLOGY CHILLER REPLACEMENT CECIL COUNTY PUBLIC SCHOOLS

100% IAC SUBMISSION 03/24/2023

MVSWG MCC-CUP MECS

MVSWG(M) MCC-CUP(M)